

# Megapixel Cube Network Camera

## 1280 x 800



- Compact and Streamline Design.
- Built-in MIC
- EasyConfig for Easy Set Up and GUI Integration
- MPEG-4, MJPEG and H.264 Triple Codec Compression
- 802.11b/g/n Wireless Connectivity (WCB-100Ae)
- WPS Supported for Easy Wireless Network Setup (WCB-100Ae)

## CB-100Ae

The compact Brickcom CB-100Ae cube network series offers a high quality, video surveillance solution for residences and small businesses. Unlike a general webcam, this camera series is a standalone surveillance system that does not need to be connected to a computer. EasyLink™ is a feature of the CB-100Ae camera which allows for users to simply plug in the camera to any home or small business network and play the video.

This camera series offers a user-friendly and unique design which allows anyone without a technical background to use it. It features live video feed and one-way audio which can be used over a local area network (LAN), through any internet browser, or via any 3G mobile device. The wireless capability makes it easy to mount on any surface. The CB-100Ae features many cutting edge functions and its fashionable, streamline design make it the perfect additional for any home or office.

Because of its many advanced features, the CB-100Ae has many versatile applications. Users can easily monitor the safety of their family members, pets, office, valuables, and property.



### **Pet Monitor:**

The motion detection feature can be used to create forbidden areas in the home which the pet should not enter when the owner is away. If the camera records the pet entering the region, a recorded message can be programmed to play and the owner will be notified via email or MMS.



### **Elderly and Child Care:**

A high concern for many people is the safety of elderly relatives and small children. Users can use the CB-100Ae camera to ensure the safety of their loved ones by use of the live view and intercom functions.



### **Small Office Surveillance:**

Security systems for small offices can be expensive and difficult to install and maintain. With the EasyConfig software, the CB-100Ae can easily be installed and configured by anyone without extensive technical knowledge. The video can be reviewed remotely so business owners can monitor office safety and employee productivity at all times.

## CB-100Ae Series

### Product Name

Megapixel Cube Network Camera

### Model Number

**CB-100Ae** - Ethernet, 1-way audio

**WCB-100Ae** - Ethernet or WiFi, 1-way audio

### Hardware System

CPU: 500 MHz

Flash: 16M

RAM: 64M DDR

### Image Sensor

Sensor Type : 1/4" Mega-Pixel CMOS Sensor

Sensor Resolution : 1280 x 800 pixel

### Minimum Illumination

1 Lux

### Lens

Lens Type : Board Lens

Focal Length: f= 3.60 mm

View Angle : H: 55.7°

V: 36.5°

F-number: F2.3

### Video

Auto Exposure Control / Auto White Balance /

Auto Gain Control

Image Compression :

H.264 / MPEG4 / MJPEG

### Max Image Resolution :

- 1280 x 800: 30fps

### Audio

1-way audio

Built-in MIC

### Network

Ethernet : one 10/100Mbps RJ-45

WiFi: 802.11 b/g/n (WCB-100Ae)

Supported Protocols : TCP/IP, UDP, ICMP, DHCP,

NTP, DNS, DDNS, SMTP, FTP, HTTP, Samba,

PPPoE, UPnP, Bonjour, RTP, RTSP, RTCP

### Interface & Buttons

DC Power Connector

Ethernet Cable Connector

Privacy Button

WPS Button

Reset Button

Microphone

### LEDs

**WCB-100Ae** - Power /Connect/Internet/ Privacy/WPS

**CB-100Ae** - Power /Connect/Internet/ Privacy

/Firmware upgrade

### Power

Input : DC12V / 1 A (Power Supply)

### Max Power consumption

CB-100Ae: 3.3 w

WCB-100Ae: 3.7 w

### Environment

Operating Temperature : 0°C ~ 50°C (32°F ~122°F)

Operating Humidity : 10% ~ 80%

### Dimension

29 (L) X60 (W) X 95 (H) mm

### Weight

CB-100A: 82g

WCB-100A: 89g


(excluding stand)

### Certification

FCC,CE

### Warranty

Limited 2-year warranty



© Brickcom Technology Inc. All Rights Reserved. This document is for planning purposes only, and is not intended to modify or supplement any specifications or warranties relating to products of Brickcom Technology. Brickcom may make changes to specifications and descriptions at any time, without notice.

**Brickcom Corporation Headquarters**  
 Address: No. 1, Jen Ai Rd., Hsinchu Industrial Park, Hukou, Hsinchu, Taiwan, R.O.C. 303  
 Tel: +886-3-5982022 Fax: +886-3-5982023  
 Mail: info@brickcom.com http://www.brickcom.com